

DATASHEET

S01.01.01.349_MAXWELL-24-T2M-CC(SS-50X50-24-T2M)

STREET LIGHT LENS:

IESNA Type II (medium) beam .

50x 50 mm, 24 lens for up to 3030 size LED packages.


1.General Information

Lens Material	: PC
Size	: 50X50mm
typ.FWHM	: Asymmetric
Design LED	: Luxeon 3030 square
Compatibility	: 3030/2835
typ.Efficiency	: 96%
Fasten	: Screw
IP class	: N/A
Zhaga	: N/A
RoHS	: YES
Color	: Clear



2.MECHANICAL SPECIFICATION

UNIT:mm



Dimensions with unmarked tolerances refer to GBT14486 tolerance table.

3. OPTICAL RESULTS

1) PHOTOMETRIC DATA(MEASURED):



LED model Luxeon 3030 square


Light colour White

LEDs/each optic 1

FWHM Asymmetric

Required components:

Glass



4.Usage and Maintenance

- 1) If necessary, clean lenses with mild soap, water and soft cloth.
- 2) Never use any commercial cleaning solvents on lenses, like alcohol.
- 3) Please handle lens with wearing gloves, skin oils may damage lens or its optical characteristic.
- 4) Short-term use maximum tolerable lens temperature: 125℃
- 5) Long-term use maximum tolerable lens temperature: 110℃

5.Note

Please test the data again before using. The chart data is for reference only.

The appearance and specifications of the product can be changed to improve the quality and/or performance without notice.

SUNLUMIN OPTICS CO., LTD

501D, Plant 2, No.30, Liuhe Road, Liuyue Community,
Henggang Str, Longgang District, Shenzhen

E
info@sunlumin-optics.com

www.
sunlumin.com www.
sunlumin-optics.com