

SunLumin[®]

Your Optical
Solution Partner



2025 Version

CATALOGUE

Content

01

Customize Solution 02

02

Street & Area Lighting
MAXWELL

MAXWELL-4_3535	05
MAXWELL-6_3535	05
MAXWELL-8_3535	05
MAXWELL-4	05
MAXWELL-6	06
MAXWELL-8	06
MAXWELL-10	06
MAXWELL-12	06
MAXWELL-12_3030	07
MAXWELL-16	07
MAXWELL-24	07
PLANCK-16	07
TESLA	
TESLA-2X3	08
TESLA-IP-24	08
COULOMB	08
AMBER	
AMBER-6	08
AMBER-IP-12	08
FRANKLIN	
FRANKLIN-12	08
FRANKLIN-24	09
FERMI	
FERMI-8	09
FERMI-24	09
FERMI-27	09
FERMI-46	09
FARADAY	
FARADAY-28	09
FARADAY-64	10
FARADAY-80	10
FARADAY-96	10
RUTHERFORD	10
RUTHERFORD-G2	10

03

Sports Light Lens

SPORT-4 11

ARISTOTLE

ARISTOTLE-58	11
ARISTOTLE-336	11
ARISTOTLE-230	11

HAWKING 11

04

UFO Light lens

UFO

UFO H

UFO-D184-H56	12
UFO-D226-H56	12
UFO-D263-H70	12
UFO-D265-H56	12
UFO-D293-H70	12

UFO C

UFO-D184-C26	13
UFO-D224-C30	13

UFO-D226-C26	13
UFO-D263-C26	13
UFO-D263-C32	13
UFO-D265-C26	13
UFO-D265-C49	13
UFO-D293-C26	14
UFO ZM	14
UFO DOB	14
UFO CE	
UFO-CE-D164-C24	14
UFO-CE-D184-C24	14
UFO-CE-D226-C26	14
UFO-CE-D266-C26	14
UFO N	
UFO-D183-120	15
UFO-D233-226	15
UFO-D263-254	15
UFO-D293-218	15
UFO N G2	
UFO-D265-C55	15

05

Architecture Lighting

SNELL 16

HILBERT

HILBERT	16
HILBERT-G2	16

HOOK

HOOK	16
HOOK-D52	16
HOOK-66	16
HOOK-BIO	16

RGBW

RGBW-D31	17
RGBW-D37	17
RGBW-D45	17
RGBW-ECO	17

HEISENBERG 17

EINSTEIN

EINSTEIN	17
EINSTEIN-6	18

HERTZ

HERTZ	18
HERTZ_5050	18

BORN 18

DARWIN

DARWIN	19
DARWIN-16	19

NOBEL 19

AMPERE

AMPERE	19
AMPERE-9	20
AMPERE-IP-9	20

DOPPLER 20

KELLY 20

BOHR 20

LONGPING

LONGPING-G1	20
LONGPING-G2	21

EDISON 21

KIRCHHOFF 21

06

Linear Lenses

CURIE

CURIE	22
CURIE-G2	22

LAPLACE-3R

LAPLACE-3R	22
LAPLACE-3R-G2	22

THOMSON

THOMSON-3	23
THOMSON-4	23
THOMSON-7	23

DAVY 23

AVOGADRO 23

07

Extrusion Linear Lens

OERSTED

OERSTED-26	24
OERSTED-40	24

08

Commercial Lighting

YOUYOU-G2

YOUYOU-D28-G2	25
YOUYOU-D35-G2	25
YOUYOU-D45-G2	25
YOUYOU-D62-G2	25

DALTON

DALTON-D22	25
DALTON-D28	25
DALTON-D35	26
DALTON-D45	26
DALTON-D55	26
DALTON-D62	26
DALTON-D75	26

HUBBLE

HUBBLE-D43	27
HUBBLE-D69	27
HUBBLE-D75	27

COMPTON 27

VOLTA 27

VOLTA-D70	27
-----------	----

09

LED Backlight & TV Lens

KEPLER

KEPLER	28
KEPLER-T	28
KEPLER-F	28

10

Glass Light Lens

LIPPMANN

LIPPMANN-D78	29
LIPPMANN-D82	29


ZEEMAN

ZEEMAN-10	30
ZEEMAN-12	30


SunLumin Customize Solution

Research & Development


Dedicated optical engineers
Dedicated mechanical engineers
Dedicated project management engineers
Turn around time: within 16-43 days



Customize Advantage



Customization



Contact Us

Sales Representatives			
Brazil	Fabio Takanohashi	ftakanohashi@sunlumin-optics.com	+55 11 9 3020 0650
Brazil	Rafael Cartoni	Rafael.Cartoni@sunlumin-optics.com	+55 11 9 8932 9031
Brazil	Aline Nunes	aline@sunlumin-optics.com	+55 11 9 4899 4028
Turkey	Zekeriya Boz	z.boz@sunlumin-optics.com	+90 546 291 2444
Russia	Saken Jusupov	saken.jusupov@sunlumin-optics.com	+7 911 758 9554
Mexico	Fransisco Sanchez	fransisco.sanchez@sunlumin-optics.com	+52 833 265 0555
Argentina	Mauricio Jancic	mauricio.jancic@sunlumin-optics.com	+54 911 3644 0385
Other countries	Mark Chen	mark.chen@sunlumin-optics.com	+86 134 8075 1201

Inside Sales			
China	Susie Huang	susie.huang@sunlumin-optics.com	+86 135 1064 2485

India Office			
India	RNPAL	r.n.pal@sunlumin-optics.com	+91 921 219 3569
India	Mark Chen	mark.chen@sunlumin-optics.com	+86 134 8075 1201


Customer Service & Complaint			
All countries		service@sunlumin-optics.com	+86 185 9423 2308

Common Beam Type Abbreviations

Name	Beam Type
30, 60, 90 etc.	beam angle in degrees
A	Asymmetric
DA	Double asymmetric
N	Narrow
M	Medium
W	Wide
T2S-CA, CB, CC etc.	T2S cutoff type A/B/C etc.
T2S-SA, SB, SC etc.	T2S semicutoff type A/B/C etc.
T2M-NA, NB, NC etc.	T2M Noncutoff type A/B/C etc.
FR01	Railway Light

Street & Area Lighting

A MAXWELL-4_3535	I MAXWELL-12_3030	P FRANKLIN-12	W FARADAY-80
B MAXWELL-6_3535	J MAXWELL-16	Q FRANKLIN-24	X FARADAY-96
C MAXWELL-8_3535	K MAXWELL-24	R FERMI-8	Y PLANCK
D MAXWELL-4	L TESLA-2X3	S FERMI-24	Z RUTHERFORD
E MAXWELL-6	M TESLA-IP-24	T FERMI-27/46	AA RUTHERFORD-G2
F MAXWELL-8	N AMBER-6	U FARADAY-28	AB COULOMB
G MAXWELL-10	O AMBER-IP-12	V FARADAY-64	
H MAXWELL-12			



Street & Area Lighting

MAXWELL

50 x 50 mm modular solutions. The most versatile modular product family especially designed for street and area lighting, but also suitable for wide range of other applications.

MAXWELL-4_3535

50 x 50 mm 2X2 arrays optimized for 3535 size LED packages. The position of LED and the positioning column meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-4-15_3535	50X50	4	15	91
MAXWELL-4-50X50_3535	50X50	4	50X50	94
MAXWELL-4-60_3535	50X50	4	60	94
MAXWELL-4-FR01_3535	50X50	4	Asymmetric	91
MAXWELL-4-T2S-CB_3535	50X50	4	Asymmetric	95
MAXWELL-4-T2S-CE_3535	50X50	4	Asymmetric	94
MAXWELL-4-DN_3535	NEW 50X50	4	Asymmetric	95

MAXWELL-6_3535

50 x 50 mm 2X3 arrays optimized for 3535 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-6-T2S-CC_3535	50X50	6	Asymmetric	95
MAXWELL-6-T2M-NA_3535	NEW 50X50	6	Asymmetric	92
MAXWELL-6-T3M-NA_3535	NEW 50X50	6	Asymmetric	89
MAXWELL-6-LN_3535	NEW 50X50	6	Asymmetric	95

MAXWELL-8_3535

50 x 50 mm 8 lens (3+2+3) arrays optimized for 3535 size LED packages. The position of LED and the positioning column meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-8-60_3535*/**	50X50	8	60	94
MAXWELL-8-90_3535*/**	50X50	8	90	94
MAXWELL-8-T2S-CB_3535***	50X50	8	Asymmetric	94
MAXWELL-8-LN_3535***	NEW 50X50	8	Asymmetric	95
MAXWELL-8-LN2_3535	NEW 50X50	8	Asymmetric	92
MAXWELL-8-SCL_3535	NEW 50X50	8	Asymmetric	94

* HV models are available, with different positioning pin, suitable for high voltage circuit design.

** PC/PMMA material available.

*** PMMA/PMMA HT material available.

MAXWELL-4

50 x 50 mm 2X2 arrays optimized for flat 5050 size LED packages. The position of LED and the positioning column meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-4-30	50X50	4	30	91
MAXWELL-4-60	50X50	4	60	93
MAXWELL-4-90	50X50	4	90	93
MAXWELL-4-120A	50X50	4	120	93
MAXWELL-4-30X100	50X50	4	30X100	93
MAXWELL-4-60X90	50X50	4	60X90	92
MAXWELL-4-T2S-CB	50X50	4	Asymmetric	93
MAXWELL-4-T2M-CA	50X50	4	Asymmetric	92
MAXWELL-4-T2M-CD	NEW 50X50	4	Asymmetric	96
MAXWELL-4-T3M-CA	50X50	4	Asymmetric	93
MAXWELL-4-T4M-CA	50X50	4	Asymmetric	93
MAXWELL-4-PX	NEW 50X50	4	Asymmetric	93



MAXWELL-4_3535



MAXWELL-6_3535



MAXWELL-8_3535




MAXWELL-4

Street & Area Lighting

MAXWELL-6

50 x 50 mm 2X3 arrays for flat 5050 size LED packages.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-6-30		50X50	6	30	96
MAXWELL-6-60		50X50	6	60	96
MAXWELL-6-90		50X50	6	90	96
MAXWELL-6-120C		50X50	6	120	93
MAXWELL-6-60X90		50X50	6	60X90	92
MAXWELL-6-T5		50X50	6	T5	93
MAXWELL-6-T2M-CB		50X50	6	Asymmetric	94
MAXWELL-6-T2M-CE	NEW	50X50	6	Asymmetric	90
MAXWELL-6-T3M-CB	NEW	50X50	6	Asymmetric	90



MAXWELL-8

50 x 50 mm 8 lens (3+2+3) arrays for up to flat 5050 size LED packages. The position of LED meet the EU ZHAGA standard.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-8-30**		50X50	8	30	93
MAXWELL-8-60**		50X50	8	60	95
MAXWELL-8-90**		50X50	8	90	96
MAXWELL-8-120B***		50X50	8	120	95
MAXWELL-8-15X60	NEW	50X50	8	15X60	95
MAXWELL-8-30X48	NEW	50X50	8	30X48	95
MAXWELL-8-60X90		50X50	8	60X90	92
MAXWELL-8-90X120		50X50	8	90X120	92
MAXWELL-8-T2***	NEW	50X50	8	Asymmetric	91
MAXWELL-8-T2S-CC***		50X50	8	Asymmetric	95
MAXWELL-8-T3M-CB	NEW	50X50	8	Asymmetric	93
MAXWELL-8-T4***		50X50	8	Asymmetric	83
MAXWELL-8-A50	NEW	50X50	8	Asymmetric	89

**PC/PMMA/PMMA HT material available.

***PMMA/PMMA HT material available.



MAXWELL-10

50 x 50 mm 10 lens (2X4+2) arrays optimized for flat 5050 size LED packages. Second generation lens.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-10-60	NEW	50X50	10	60	93
MAXWELL-10-90	NEW	50X50	10	90	93
MAXWELL-10-T2S-CD	NEW	50X50	10	Asymmetric	93
MAXWELL-10-T2M-SC		50X50	10	Asymmetric	92
MAXWELL-10-T3M-SB		50X50	10	Asymmetric	92



MAXWELL-12

50 x 50 mm 12 lens (2X5+2) arrays optimized for flat 5050 size LED packages.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
MAXWELL-12-60	NEW	50X50	12	60	94
MAXWELL-12-90	NEW	50X50	12	90	94
MAXWELL-12-T1S	NEW	50X50	12	Asymmetric	93
MAXWELL-12-T2S-CF	NEW	50X50	12	Asymmetric	93
MAXWELL-12-T2M-SC**		50X50	12	Asymmetric	97

**PC/PMMA material available.



Street & Area Lighting

MAXWELL-12_3030

50 x 50 mm 12 lens arrays optimized for flat 3030 size LED packages. Variant with improved LED distance.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff
MAXWELL-12-20_3030	50X50	12	20	94
MAXWELL-12-40_3030	50X50	12	40	94
MAXWELL-12-60_3030	50X50	12	60	94
MAXWELL-12-90_3030	50X50	12	90	94
MAXWELL-12-T2M-CD_3030	50X50	12	Asymmetric	93
MAXWELL-12-T2M-SC_3030	50X50	12	Asymmetric	94
MAXWELL-12-T3M-SC_3030	50X50	12	Asymmetric	93

MAXWELL-16

50 x 50 mm 4X4 arrays optimized for 3030 size LED packages. The position of LED and the positioning column meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff
MAXWELL-16-15	50X50	16	15	93
MAXWELL-16-20	50X50	16	20	93
MAXWELL-16-30	50X50	16	30	95
MAXWELL-16-40	50X50	16	40	93
MAXWELL-16-60	50X50	16	60	93
MAXWELL-16-90	50X50	16	90	93
MAXWELL-16-45X90	50X50	16	45X90	93
MAXWELL-16-T5	50X50	16	T5	93
MAXWELL-16-A45	50X50	16	Asymmetric	94
MAXWELL-16-A50	50X50	16	Asymmetric	95
MAXWELL-16-T1S	50X50	16	Asymmetric	93
MAXWELL-16-T2S-CA	50X50	16	Asymmetric	93
MAXWELL-16-T2M-CB	50X50	16	Asymmetric	93
MAXWELL-16-T2M-CD	50X50	16	Asymmetric	96
MAXWELL-16-T2M-SD	50X50	16	Asymmetric	90
MAXWELL-16-T3M-CA	50X50	16	Asymmetric	95

MAXWELL-24

50 x 50 mm 24 lens arrays optimized for 3030 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff
MAXWELL-24-15	50X50	24	15	92
MAXWELL-24-20	50X50	24	20	94
MAXWELL-24-30	50X50	24	30	92
MAXWELL-24-45	50X50	24	45	94
MAXWELL-24-60	50X50	24	60	95
MAXWELL-24-90	50X50	24	90	93
MAXWELL-24-120B	50X50	24	120	92
MAXWELL-24-A45	50X50	24	Asymmetric	92
MAXWELL-24-T2M-CC	50X50	24	Asymmetric	96
MAXWELL-24-T2M-CB	50X50	24	Asymmetric	93
MAXWELL-24-T3M-CA	50X50	24	Asymmetric	94

PLANCK-16

Economic version lens module for street, area and industry lighting, 100X60mm, IP66, 16 lens module. Up to 3535 LEDs.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff
PLANCK-16-T2S-NA	100X60	16	Asymmetric	92



MAXWELL-12_3030



MAXWELL-16



MAXWELL-24



PLANCK-16

Street & Area Lighting

TESLA

TESLA-2X3

62 x 30 mm modular solutions. 2X3 arrays for up to 5050 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
TESLA-2X3-T2M-CB	62X30	6	Asymmetric	95

TESLA-IP-24

135X100mm; IP66 with a silicone gasket; 24 lens arrays for 5050 size LED packages

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
TESLA-IP-24-60	135X100	24	60	93
TESLA-IP-24-90	135X100	24	90	93
TESLA-IP-T2M-CA	135X100	24	Asymmetric	93

COULOMB

90X90mm ingress protected 4 lens arrays with a silicone gasket optimized for flat 7070 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
COULOMB-4-90	90X90	4	90	95

AMBER

Amber color material eliminate blue light

AMBER-6

2x3 Lens arrays with 5050 size LED package; amber color material eliminate blue light.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
AMBER-6-T2M-CB	COMING 50X50	6	Asymmetric	95

AMBER-IP-12

173 x 71 mm ingress protected 2X6 arrays with a silicone gasket for up to flat 5050 size LED packages. Meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
AMBER-IP-12-90	173X71	12	90	80

FRANKLIN

173 x 71 mm modular solutions. IP66 with silicone gasket; The most versatile modular product family especially designed for street lighting and area lighting, but also suitable for wide range of other applications.


FRANKLIN-12

173 x 71 mm, 2X6 arrays for up to flat 5050 size LED packages. Meet the EU ZHAGA standard.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FRANKLIN-12-30	173X71	12	30	95
FRANKLIN-12-60	173X71	12	60	95
FRANKLIN-12-90	173X71	12	90	95
FRANKLIN-12-T2S-CB	173X71	12	Asymmetric	93
FRANKLIN-12-T2M-CA	173X71	12	Asymmetric	93
FRANKLIN-12-T2M-CD	173X71	12	Asymmetric	90
FRANKLIN-12-T3M-CA	173X71	12	Asymmetric	93



TESLA-2X3



TESLA-IP-24



COULOMB



AMBER-IP-12



FRANKLIN-12

Street & Area Lighting

FRANKLIN-24

173 x 71 mm, 3X8 arrays for up to flat 5050 size LED packages

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FRANKLIN-24-30	173X71	24	30	93
FRANKLIN-24-60	173X71	24	60	93
FRANKLIN-24-90	173X71	24	90	93
FRANKLIN-24-T2M-CB	173X71	24	Asymmetric	94
FRANKLIN-24-T3	NEW 173X71	24	Asymmetric	90
FRANKLIN-24-T4	173X71	24	Asymmetric	89
FRANKLIN-24-DWC	COMING 173X71	24	Asymmetric	89
FRANKLIN-24-SCL	COMING 173X71	24	Asymmetric	89
FRANKLIN-24-ME	COMING 173X71	24	Asymmetric	89
FRANKLIN-24-VSM	COMING 173X71	24	VSM	89

FERMI

Multi-modular solutions, special for Brazil market.

FERMI-8

50 x 50 mm 8 lens (2X4) arrays optimized for flat 5050 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FERMI-8-60	50X50	8	60	96
FERMI-8-90	50X50	8	90	96
FERMI-8-120C	50X50	8	120	96
FERMI-8-T2M-CB	50X50	8	Asymmetric	94
FERMI-8-T3M-CA	50X50	8	Asymmetric	93

FERMI-24

173 x 71 mm, IP66 with a silicone gasket, 6X4 arrays for up to flat 5050 size LED packages

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FERMI-24-T2M-CC	173X71	24	Asymmetric	93

FERMI-27

220 x 78 mm ingress protected 27 lens arrays with a silicone gasket for up to flat 5050 size LED packages

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FERMI-27-T2M-CD	220X78	27	Asymmetric	90

FERMI-46

220X110mm,IP66 with a silicone gasket, 46 lens arrays for up to flat 5050 size LED packages

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FERMI-46-T2M-CD	220X110	46	Asymmetric	93

FARADAY

Width 70 mm IP66 modular lens solutions;

FARADAY-28

236 x 70 mm with 28 lens arrays; Reach IP66 with silicone gasket; Design base on flat 5050 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FARADAY-28-30	236X70	28	30	92
FARADAY-28-60	236X70	28	60	92
FARADAY-28-90	236X70	28	90	92
FARADAY-28-T2S-CD	236X70	28	Asymmetric	93
FARADAY-28-T2M-SB	236X70	28	Asymmetric	93
FARADAY-28-T3M-NC	236X70	28	Asymmetric	93
FARADAY-28-A55	236X70	28	Asymmetric	93



FRANKLIN-24



FERMI-8



FERMI-24



FERMI-27



FERMI-46



FARADAY-28

Street & Area Lighting

FARADAY-64

236 x 70 mm with 64 lens arrays; Reach IP66 with silicone gasket; Design base on flat 3030 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FARADAY-64-30	236X70	64	30	93
FARADAY-64-60	236X70	64	60	93
FARADAY-64-90	236X70	64	90	93
FARADAY-64-70X120	236X70	64	70X120	93
FARADAY-64-T2S-CC	236X70	64	Asymmetric	93
FARADAY-64-T2M-CB	236X70	64	Asymmetric	93



FARADAY-80

234 x 70 mm with 80 lens arrays; Reach IP66 with silicone gasket; Design base on flat 3030 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FARADAY-80-60	234X70	80	60	94
FARADAY-80-90	234X70	80	90	93
FARADAY-80-35X95	234X70	80	35X95	93



FARADAY-96

252 x 70 mm with 96 lens arrays; Reach IP66 with silicone gasket; Design base on flat 3030 size LED package.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
FARADAY-96-30	COMING	252X70	96	30	93
FARADAY-96-60	NEW	252X70	96	60	92
FARADAY-96-90	NEW	252X70	96	90	92
FARADAY-96-30X70	COMING	252X70	96	30X70	93
FARADAY-96-45X90	COMING	252X70	96	45X90	93
FARADAY-96-T2M-CA	COMING	252X70	96	Asymmetric	93
FARADAY-96-T3M-CA	COMING	252X70	96	Asymmetric	93



RUTHERFORD

Integrated with Ingress protected power supply chamber cover and light source chamber; IP66 with silicone gasket; Optimized for 3030 size LED packages. For different wattages, has excellent waterproof ability. Compatible with 2835 LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
RUTHERFORD-72-T2S-CD	325X110	72	Asymmetric	94
RUTHERFORD-120-T2S-CD	375X128	120	Asymmetric	94
RUTHERFORD-192-T2S-CD	433X145	192	Asymmetric	94




RUTHERFORD-G2

T2M cutoff, meet Brazil Immetro certification light distribution requirement. Integrated with Ingress protected power supply chamber cover and light source chamber; IP66 with silicone gasket; Optimized for 2835 size LED packages. For different wattages, has excellent waterproof ability. Compatible with 3030 LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
RUTHERFORD-64-T2M-CC_G2	NEW 223X130	64	T2M	90
RUTHERFORD-112-T2M-CC_G2	NEW 304X134	112	T2M	90
RUTHERFORD-192-T2M-CC_G2	NEW 355X185	192	T2M	90
RUTHERFORD-280-T2M-CC_G2	NEW 420X210	280	T2M	90
RUTHERFORD-384-T2M-CC_G2	NEW 495X245	384	T2M	90



Sports Light Lens



SPORT-4

50 x 50 mm 2X2 arrays optimized for HP 3535 and compatible with up to 5050 size LED packages.
The position of LED and the positioning column meet the EU ZHAGA standard

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
SPORT-4-10	NEW	50X50	4	10	93
SPORT-4-A40N	COMING	50X50	4	Asymmetric	93
SPORT-4-A50N-A		50X50	4	Asymmetric	92
SPORT-4-A05N		50X50	4	Asymmetric	93
SPORT-4-A05M		50X50	4	Asymmetric	93
SPORT-4-A05W		50X50	4	Asymmetric	93
SPORT-4-A60N-A		50X50	4	Asymmetric	93
SPORT-4-A60N-B		50X50	4	Asymmetric	93
SPORT-4-A60W		50X50	4	Asymmetric	93

ARISTOTLE

ARISTOTLE-58

252x119mm ingress protected 58 lens arrays with a silicone gasket optimized for flat 5050 size LED packages.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
ARISTOTLE-58-30	252X119	58	30	93
ARISTOTLE-58-60	252X119	58	60	93

ARISTOTLE-336

360X172mm, IP66 with silicone gasket; 336 lens arrays for up to flat 3030 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
ARISTOTLE-336-18	360X172	336	18	93
ARISTOTLE-336-25	360X172	336	25	93
ARISTOTLE-336-45	360X172	336	45	93
ARISTOTLE-336-60	360X172	336	60	93

ARISTOTLE-230

481X231mm, IP66 with silicone gasket; 230 lens arrays for up to flat 5050 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
ARISTOTLE-230-20*	481X231	230	20	93
ARISTOTLE-230-30	481X231	230	30	93
ARISTOTLE-230-60	481X231	230	60	93

*FWHM: 15 degree based on OSRAM-P3737

HAWKING


520X116mm, IP66 with silicone gasket; 96 lens arrays for up to flat 5050 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
HAWKING-96-20*	520X116	96	20	90
HAWKING-96-40	520X116	96	40	90
HAWKING-96-60	520X116	96	60	90
HAWKING-96-90	520X116	96	90	93
HAWKING-96-A50N-B	520X116	96	Asymmetric	93

*FWHM: 10 degree based on OSRAM-P3737



UFO Light Lens



UFO H

UFO H SERIES is the versatile round lens series with open hole in the middle for sensor, free arrangement of LEDs and high efficiency.

UFO-D184-H56

Ø184 mm; 4 rings Convex lens structure and free arrangement of LEDs. With Open Hole (Ø56mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D184-4R-60A-H56	D184	4R	60	96
UFO-D184-4R-90A-H56	D184	4R	90	96
UFO-D184-4R-120B-H56	D184	4R	110	94

UFO-D226-H56

Ø226 mm; 6 rings Convex lens structure and free arrangement of LEDs. With Open Hole (Ø56mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D226-6R-60A-H56	D226	6R	60	96
UFO-D226-6R-90A-H56	D226	6R	90	96
UFO-D226-6R-120A-H56	D226	6R	110	96

UFO-D263-H70

Ø263 mm; 8 rings Convex lens structure and free arrangement of LEDs. With Open Hole (Ø70 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D263-8R-90A-H70	D263	8R	85	93

UFO-D265-H56


Ø265 mm; 8 rings Convex lens structure and free arrangement of LEDs. With Open Hole (Ø56 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D265-8R-60A-H56	D265	8R	60	96
UFO-D265-8R-90A-H56	D265	8R	90	96
UFO-D265-8R-120B-H56	D265	8R	120	94

UFO-D293-H70

Ø293 mm; 8 rings Convex lens structure and free arrangement of LEDs. With Open Hole (Ø70 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D293-9R-60A-H70	D293	9R	60	92
UFO-D293-9R-90A-H70	D293	9R	90	92
UFO-D293-9R-120A-H70	D293	9R	120	92



UFO Light Lens

UFO C

UFO C SERIES is the versatile round lens series with Confined space in the middle for sensor. The lamp beads can be arranged freely, and a high-efficiency UFO lens series.

UFO-D184-C26

Ø184 mm; 6 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D184-6R-60A-C26	D184	6R	60	96
UFO-D184-6R-90A-C26	D184	6R	90	96
UFO-D184-XX-120A-C26	D184	FLAT	120	94

UFO-D224-C30

Ø224 mm; 5 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø30 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D224-5R-60A-C30	D224	5R	60	90
UFO-D224-5R-90A-C30	NEW D224	5R	90	90
UFO-D224-XX-120A-C30	D224	FLAT	120	93

UFO-D226-C26

Ø226 mm; 7 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D226-7R-60A-C26	NEW D226	7R	60	96
UFO-D226-7R-90A-C26	D226	7R	90	96
UFO-D226-XX-120A-C26	NEW D226	FLAT	120	96

UFO-D263-C26

Ø263 mm; 11 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D263-11R-60A-C26	D263	11R	60	93
UFO-D263-11R-90A-C26	D263	11R	85	93

UFO-D263-C32

Ø263 mm; 6 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø32 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D263-6R-60A-C32	D263	6R	60	90

UFO-D265-C26

Ø265 mm; 8 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D265-8R-30A-C26	D265	8R	30	88
UFO-D265-8R-60A-C26	D265	8R	60	96
UFO-D265-8R-90A-C26	D265	8R	90	96
UFO-D265-XX-120A-C26	D265	FLAT	120	96

UFO-D265-C49

Ø265 mm; 8 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø49 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D265-8R-30A-C49	D265	8R	30	88
UFO-D265-8R-60A-C49	D265	8R	60	92
UFO-D265-8R-90A-C49	D265	8R	90	92
UFO-D265-XX-120A-C49	D265	FLAT	120	96



UFO-D224-C30



UFO-D263-C26



UFO-D265-C26



UFO-D265-C49

UFO Light Lens

UFO-D293-C26

Ø293 mm; 12 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-D293-12R-60A-C26	D293	12R	60	92
UFO-D293-12R-90A-C26	D293	12R	90	92
UFO-D293-12R-120A-C26	D293	12R	120	92



UFO-D293-C26

UFO ZM

Adjustable (ZOOM) angle UFO lens series, free switch to 60°/90°/110°, up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-ZM-D182-9R-C40	D182	9R	60/90/110	90
UFO-ZM-D224-12R-C52	D224	12R	60/90/110	90
UFO-ZM-D262-15R-C52	D262	15R	60/90/110	90



UFO ZM

UFO DOB

With a space in the middle large enough to house a DOB (Driver On Board) driver solutions. LED free layout, up to 3030 size LED package

Name	Dimensions	Ring Qty	Typ.FWHM	Typ.Eff.
UFO-DOB-D184-3R-90A-C76	D184	3R	90	94
UFO-DOB-D226-4R-90A-C96	D226	4R	90	94
UFO-DOB-D265-5R-90A-C109	D265	5R	90	94



UFO DOB


UFO CE

Update UFO version, Cost optimize high optical efficiency with the convex lens structure and more circles free arrangement of lamp beads. With Confined space in the middle sensor.

UFO-CE-D164-C24

7 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø24 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-CE-D164-7R-60A-C24	D164	7	60	90
UFO-CE-D164-7R-90A-C24	D164	7	90	90




UFO-CE-D164-C24

UFO-CE-D184-C24

9 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø24 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-CE-D184-9R-60A-C24	D184	9	60	90
UFO-CE-D184-9R-90A-C24	D184	9	90	90



UFO-CE-D184-C24

UFO-CE-D226-C26

11 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-CE-D226-11R-60A-C26	D226	11	60	90
UFO-CE-D226-11R-90A-C26	D226	11	90	90




UFO-CE-D226-C26

UFO-CE-D265-C26

14 rings Convex lens structure and free arrangement of LEDs. With Confined Space (Ø26 mm) in the middle for sensor. Up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-CE-D265-14R-60A-C26	D265	14	60	90
UFO-CE-D265-14R-90A-C26	D265	14	90	90



UFO-CE-D265-C26

UFO Light Lens

UFO N

UFO N SERIES is the most popular UFO lens series with many individual convex-optics, delivers low UGR.

UFO-D183-120
Ø183 mm; 120 pcs LED Domes array for industrial lighting, up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-D183-120-60B-C17	D183	120	60	90
UFO-D183-120-90B-C17	D183	120	90	90
UFO-D183-XX-120A-C17	D183	FREE	FLAT	90

UFO-D233-226
Ø233 mm; 226 pcs LED Domes array for industrial lighting, up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-D233-226-60B-C17	D233	226	60	90
UFO-D233-226-90B-C17	D233	226	90	90
UFO-D233-XX-120A-C17	D233	FREE	FLAT	90

UFO-D263-254
Ø263 mm; 254 pcs LED Domes array for industrial lighting, up to 3030 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-D263-254-60B-C20	D263	254	60	90
UFO-D263-254-90B-C20	D263	254	90	90
UFO-D263-XX-120A-C20	D263	FREE	FLAT	90

UFO-D293-218
Ø293 mm; 218 pcs LED Domes array for industrial lighting, up to 5050 size LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-D293-218-30B-C45	D293	218	30	92

UFO N G2

UFO N G2 SERIES is the most popular UFO lens series with many individual convex-optics, delivers super low UGR

UFO-D265-C55
Ø265 mm; Optimized on 4*3030 LED package, compatible with 5050 size flat LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
UFO-D265-90-30x90-C55_G2	D265	90	30X90	91



Architecture Lighting

SNELL

Ø16.1mm TIR-lenses assembled with holder. Optimized for CREE XP-G3, compatible with up to 5050 size LED packages, 3535 LED holder & 5050 LED holder is available.

Name		D	H	Typ.FWHM	Typ.Eff.
SNELL-15	NEW	D16.1	10	15	80
SNELL-25	NEW	D16.1	10	25	82
SNELL-36	NEW	D16.1	10	36	85
SNELL-55	NEW	D16.1	10	55	80
SNELL-20X60	NEW	D16.1	10	20X60	80

HILBERT

HILBERT

Ø22mm TIR-lenses up to 3535 size LED packages, assembled with holder

Name		D	H	Typ.FWHM	Typ.Eff.
HILBERT-25		D22	14.5	25	91

HILBERT-G2

Ø22mm TIR-lenses assembled with holder. Optimized for CREE XP-G3, compatible with up to 5050 size LED packages, 3535 LED holder & 5050 LED holder is available

Name		D	H	Typ.FWHM	Typ.Eff.
HILBERT-10_G2	NEW	D22	14.8	15	88
HILBERT-15_G2	NEW	D22	14.8	15	80
HILBERT-25_G2	NEW	D22	14.8	25	78
HILBERT-36_G2	NEW	D22	14.8	36	80
HILBERT-55_G2	NEW	D22	14.8	55	80
HILBERT-15X45_G2	NEW	D22	14.8	15X45	80

HOOK

Narrow beam angel for spot light and project light

HOOK

Φ35 mm single lens, Narrow beam angle with position pin, Ø37 mm with holder, holder is optional, optimized for CREE XP-E.

Name		D	H	Typ.FWHM	Typ.Eff.
HOOK-4		D37	18.75	4	93

HOOK-D52

Narrow beam angle, Optimized for CREE XPE 3535 and compatible with 3030 size LED package .

Name		D	H	Typ.FWHM	Typ.Eff.
HOOK-D52-5		D52.5	27.4	5	93

HOOK-66


Narrow beam angle, optimized for LUMISEE L35W-11C2S and compatible with 3535 size LED package. For spot light and project light.

Name		D	H	Typ.FWHM	Typ.Eff.
HOOK-66-16		66X66	40.5	16	89

HOOK-BIO

Φ36.5*45.1mm lens with holder, extreme narrow beam angle, Bio lens assembly, optimized for CREE XP-E.

Name		D	H	Typ.FWHM	Typ.Eff.
HOOK-BIO-3		D36.8	46.4	3	45



SNELL



HILBERT



HOOK



HOOK-D52



HOOK-66



HOOK-BIO

Architecture Lighting

RGBW

RGBW-D31

Ø37 mm TIR-lenses optimized for RGBW colour mixing applications , optimize for Dome 3535 size RGBW LED package.

Name	D	H	Typ.FWHM	Typ.Eff.
RGBW-D31-8	D31	16.2	8	93

RGBW-D37

Ø37 mm TIR-lenses optimized for RGBW colour mixing applications , design base on Dome 5050 size RGBW LED packages, compatible with Dome 3535 and 3030 size LED package.

Name	D	H	Typ.FWHM	Typ.Eff.
RGBW-D37-15	D37	20.3	15	93
RGBW-D37-25	D37	20.3	25	93
RGBW-D37-40	D37	20.3	40	93
RGBW-D37-50	D37	20.3	50	93
RGBW-D37-20X30	D37	20.3	20X30	93

RGBW-D45

Ø45 mm TIR-lenses for RGBW colour mixing applications and up to 5050 size RGB LED packages

Name	D	H	Typ.FWHM	Typ.Eff.
RGBW-D45-10	D45	26.2	10	90
RGBW-D45-15	D45	27.2	15	90
RGBW-D45-24	D45	27.2	24	90

RGBW-ECO

Cost Economy, Ø22 mm lens with seal protection function for outdoor lighting. optimized for CLQ6A .

Name	D	H	Typ.FWHM	Typ.Eff.
RGBW-ECO-D22-30	D22	12.4	30	93
RGBW-ECO-D22-40	D22	12.4	40	93
RGBW-ECO-D22-30X35	D22	12.7	30X35	93



HEISENBERG

Ø10 mm TIR-lenses optimized for 3535 Mid-Power or High-Power LED packages, assembled with holder.

Name	D	H	Typ.FWHM	Typ.Eff.
HEISENBERG-15	D10	7.4	15	93
HEISENBERG-24	D10	7.4	24	93
HEISENBERG-36	D10	7.7	36	93
HEISENBERG-25X40	D10	7.7	25X40	93



EINSTEIN

EINSTEIN

Ø12 mm lens optimized for 3535 LED package,compatible with up to 5050 size LED packages. With holder or without holder is optional

Name	D	H	Typ.FWHM	Typ.Eff.
EINSTEIN-15	D13.2	7.35	15	93
EINSTEIN-20	D13.2	7.35	20	93
EINSTEIN-35	D13.2	7.35	35	93
EINSTEIN-40	D13.2	7.35	40	93
EINSTEIN-75	D13.2	7.35	75	93
EINSTEIN-85	D13.2	7.35	85	93



Architecture Lighting

EINSTEIN-6

Assembly 6 EINSTEIN single lens with holder and shade, size 107.6x18.5mm, Both white / black holder and shade is available . optimized for 3535 LED package, compatible with up to 5050 size LED packages.

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
EINSTEIN-6-15	107.6X18.5	18.1	15	93
EINSTEIN-6-20	107.6X18.5	18.1	20	93
EINSTEIN-6-35	107.6X18.5	18.1	35	93
EINSTEIN-6-40	107.6X18.5	18.1	40	93
EINSTEIN-6-75	107.6X18.5	18.1	75	93
EINSTEIN-6-85	107.6X18.5	18.1	85	93



HERTZ

HERTZ

Ø15.2mm Assembled with holder and Ø13.5mm TIR-lenses. Optimized for 3535 medium or high power LED package, compatible with 5050, 3030 medium and high power LED package. Black or White holder optional; Tape optional.

Name	D	H	Typ.FWHM	Typ.Eff.
HERTZ-13	D15.2	9	13	93
HERTZ-18	D15.2	9	18	93
HERTZ-25	D15.2	9	25	93
HERTZ-70	D15.2	9	70	93
HERTZ-16X35	D15.2	9	16X35	93
HERTZ-16X55	D15.2	9	16X55	93



HERTZ_5050

Ø15.3mm Assembled with holder and Ø13.5mm TIR-lenses. Optimized for 5050 medium or high power LED package, compatible with Batwing high power LED package.

Name	D	H	Typ.FWHM	Typ.Eff.
HERTZ-30_5050	D15.3	13.3	30	93
HERTZ-35_5050	D15.3	13.3	35	90
HERTZ-40_5050	D15.3	13.3	40	75
HERTZ-50_5050	D15.3	13.3	50	90
HERTZ-55_5050	D15.3	13.3	55	90



BORN

Ø21.2 mm TIR-lenses with holder, design for 3535 LED. Compatible with up to 5050 size LED packages.

Name	D	H	Typ.FWHM	Typ.Eff.
BORN-10	D21.2	12.4	10	90
BORN-15	D21.2	12.4	15	90
BORN-25	D21.2	12.4	25	90
BORN-30	D21.2	12.4	30	90
BORN-55	D21.2	12.4	55	90
BORN-35X10	D21.2	12.4	35X10	90



Architecture Lighting

DARWIN

DARWIN

Ø232 mm TIR-lenses design base on middle power 3535 size LED package. Assembly with holder

Name	D	H	Typ.FWHM	Typ.Eff.
DARWIN-7	D23.2	13.3	7	93
DARWIN-8	D23.2	12.32	8	93
DARWIN-10	D23.2	12.32	10	93
DARWIN-12	D23.2	12.32	12	93
DARWIN-17	D23.2	12.32	17	93
DARWIN-25	D23.2	12.32	25	93
DARWIN-40	D23.2	12.32	40	93
DARWIN-60	D23.2	12.42	60	93
DARWIN-10X20	D23.2	12.2	10X20	93
DARWIN-12X45	D23.2	12.32	12X45	93
DARWIN-15X55	D23.2	12.32	15X55	93

DARWIN-16

Assembly 16 Darwin single lens (4X4) arrays with 110.7 x110.7 mm holder. Available white and black holder.

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
DARWIN-16-7	110.7X110.7	18.2	7	93
DARWIN-16-8	110.7X110.7	18.2	8	93
DARWIN-16-10	110.7X110.7	18.2	10	93
DARWIN-16-12	110.7X110.7	18.2	12	93
DARWIN-16-17	110.7X110.7	18.2	17	93
DARWIN-16-25	110.7X110.7	18.2	25	93
DARWIN-16-40	110.7X110.7	18.2	40	93
DARWIN-16-60	110.7X110.7	18.2	60	93
DARWIN-16-10X20	110.7X110.7	18.2	10X20	93
DARWIN-16-12X45	110.7X110.7	18.2	12X45	93
DARWIN-16-15X55	110.7X110.7	18.2	15X55	93

NOBEL

Ø28.9 mm single lens, Ø31 mm with holder. Designed based on CREE XPE 3535 LED, compatible with 3030 and CREE JR5050 and Batwing package by different holder.

Name	D	H	Typ.FWHM	Typ.Eff.
NOBEL-6	D31	17.1	6	93
NOBEL-9	D31	17.1	9	93
NOBEL-19	D31	17.1	19	93
NOBEL-25	D31	17.1	25	93
NOBEL-8X35	D31	17.1	8X35	93
NOBEL-9X20	D31	17.1	9X20	93
NOBEL-12X30	D31	17.1	12X30	93

AMPERE

AMPERE

Ø37 mm TIR-lenses with holder, optimize for XPE 3535 size LED package, compatible with up to 5050 size LED packages.

Name	D	H	Typ.FWHM	Typ.Eff.
AMPERE-5	D37	18.75	5	93
AMPERE-7	D37	18.75	7	93
AMPERE-9	D37	18.75	9	93
AMPERE-12	D37	18.75	12	93
AMPERE-24	D37	18.75	24	93
AMPERE-36	D37	18.75	36	93
AMPERE-45	D37	18.75	45	93
AMPERE-10X30	D37	18.75	10X30	93



Architecture Lighting

AMPERE-9

Assembly with 9 pcs (3X3 arrays) Ampere single lenses with 110.7 x110.7 mm holder.

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
AMPERE-9-4	110.7X110.7	18.7	4	93
AMPERE-9-5	110.7X110.7	18.7	5	93
AMPERE-9-7	110.7X110.7	18.7	7	93
AMPERE-9-9	110.7X110.7	18.7	9	93
AMPERE-9-12	110.7X110.7	18.7	12	93
AMPERE-9-24	110.7X110.7	18.7	24	93
AMPERE-9-36	110.7X110.7	18.7	36	93
AMPERE-9-45	110.7X110.7	18.7	45	93
AMPERE-9-10X30	110.7X110.7	18.7	10X30	93

AMPERE-IP-9

136X136mm, 3X3 Lens array modular solutions for wall washing light, optimized for 3535 medium or high power LED packages, with silicone gasket with Ip68

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
AMPERE-IP-9-7	136X136	26.5	7	93

DOPPLER

Silicone lenses designed for sports field, area lighting, 35 x 35 mm single silicone lenses, optimized for LUMILEDS LXRT7-RW50

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
DOPPLER-60	35X35	14	60	93

KELLY

KELLY series lens, wide horizontal beam, suitable for emergency, vehicle warning lighting, corridor and wall washing light.

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
KELLY-100X15	29X23	13.4	100X15	97

BOHR

BOHR series lens enables to illuminate Windows and Doors. Optimized for 3535 size LED packages.

Name	Dimensions	H	Typ.FWHM	Typ.Eff.
BOHR-3X110*	55X44	27.5	3X110	93
BOHR-D68-XX-120	D68	14	120	93


* Clear Version, high efficiency, Matt Version, RGBW version.

LONGPING


LONGPING-G1

Optimized for 3030 packages, compatible with 3535 Mid-Power or High-Power LED packages, wall washing light. With position PIN and glue fastening.


Name		D	H	Typ.FWHM	Typ.Eff.
LONGPING-11_G1	NEW	D14.9	7	11	93
LONGPING-15_G1	NEW	D14.9	7	15	93
LONGPING-20_G1		D14.9	7	20	93
LONGPING-25_G1	NEW	D14.9	7	25	93
LONGPING-30_G1		D14.9	7	30	93
LONGPING-35_G1		D14.9	7	35	93
LONGPING-30X35_G1	NEW	D14.9	7	30X35	93
LONGPING-30X45_G1		D14.9	7	30X45	93




AMPERE-9



AMPERE-IP-9



DOPPLER



KELLY



BOHR



LONGPING-G1

Architecture Lighting

LONGPING-G2

Both version design on 3030 compatible with 3535 Mid-Power or High-Power and design for flat 5050 size LED packages, wall washing light. Clip fastening.

Name	D	H	Typ.FWHM	Typ.Eff.
LONGPING-30_G2_3030	D14.9	10.4	30	93
LONGPING-30X40_G2_3030	D14.9	10.4	30X40	93
LONGPING-30_G2	D14.9	10.4	30	93
LONGPING-35X45_G2	D14.9	10.4	35X45	93



EDISON

Ø22 mm lens with integrated holder for wall washing light, optimized for middle power 3535 size LED package. compatible with 3030 size LED package.

Name	D	H	Typ.FWHM	Typ.Eff.
EDISON-12	D22	13.2	12	93
EDISON-20	D22	13.2	20	93
EDISON-30	D22	13.2	30	93
EDISON-50	D22	13.2	50	93
EDISON-60	D22	13.2	60	93
EDISON-20X30	D22	13.2	20X30	93
EDISON-15X35	D22	13.2	15X35	93
EDISON-20X40	D22	12.85	20X40	93
EDISON-25X40	D22	12.6	25X40	93




KIRCHHOFF

16*16mm lens, easily seal protection function for outdoor lighting to reach IP68 by potting glue.The economical version of the HERTZ series. Optimized for CREE XP-E, compatible with 3030 size LED packages.

Name	D	H	Typ.FWHM	Typ.Eff.
KIRCHHOFF-12	16X16	9.2	12	85
KIRCHHOFF-20	16X16	9.2	20	85
KIRCHHOFF-35	16X16	9.2	35	85
KIRCHHOFF-40	16X16	10.15	40	85
KIRCHHOFF-60	16X16	10.15	60	85
KIRCHHOFF-15X30	16X16	9.2	15X30	85
KIRCHHOFF-15X55	16X16	9.2	15X55	85



Linear Lenses



CURIE

CURIE

280×43mm linear lens, optimized for 3030 size LED package. Compatible with 2835 LED package. Fit for 24mm wide ZHAGA PCB

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
CURIE-24-60	280X43	24	60	90
CURIE-24-90B	280X43	24	90	89
CURIE-24-30X70	280X43	24	30X70	89
CURIE-XX-60X90	280X43	XX	60X90	90

CURIE-G2

280×40mm linear lens, free arrangement of LEDs, optimized for 3030 size LED package. Compatible with 2835 LED package. Fit for 24mm wide ZHAGA PCB

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
CURIE-XX-60_G2	NEW 280X40	XX	60	86
CURIE-XX-90A_G2	NEW 280X40	XX	90	86
CURIE-XX-DA25_G2	NEW 280X40	XX	Da25	86
CURIE-XX-A25_G2	NEW 280X40	XX	A25	86

LAPLACE-3R

LAPLACE-3R


285×62mm 3-row (3×11) linear lenses, TIR optics design base on 2835 size LED package. Compatible with 2835 LED package. Fit for ZHAGA 3 rows PCB.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
LAPLACE-3R-33-60	285X62	33	60	96
LAPLACE-3R-33-90A	285X62	33	90	94

LAPLACE-3R-G2

285×62mm 3-row (3×11) linear lenses, Fresnel optics design base on 2835 size LED package. Compatible with 2835 LED package. Fit for ZHAGA 3 rows PCB.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
LAPLACE-3R-33-60_G2	NEW 286X61	33	60	92.5
LAPLACE-3R-33-90B_G2	286X61	33	90	92.5



Linear Lenses

THOMSON

THOMSON is a perfect solution with a seamless glare eliminating shade and highly efficient lenses, optimized for 4*3030/4*2835 size LED packages.

THOMSON-3

120*40mm linear solution with shade-t3.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
THOMSON-3-60	120X40	3	60	92
THOMSON-3-70	120X40	3	70	93
THOMSON-3-80	120X40	3	80	83
THOMSON-3-50X70	120X40	3	50X70	87

THOMSON-4

160*40mm linear solution with shade-t4.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
THOMSON-4-30	160X40	4	30	88
THOMSON-4-60	160X40	4	60	83
THOMSON-4-80	160X40	4	80	83
THOMSON-4-50X70	160X40	4	50X70	73

THOMSON-7

280*40mm linear solution with shade-t7.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
THOMSON-7-30	280X40	7	30	88
THOMSON-7-60	280X40	7	60	83
THOMSON-7-80	280X40	7	80	83
THOMSON-7-50X70	280X40	7	50X70	73

DAVY



280*15mm linear lens, optimized for SMD2835/3030 LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
DAVY-24-30	280X15.6	24	30	90
DAVY-24-90B	280X15.4	24	90	90

AVOGADRO

280*10mm linear lens, optimized for SMD2835/3030 LED package

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
AVOGADRO-28-25	280X9.6	28	25	90
AVOGADRO-28-15X50	280X9.6	28	15X50	90



Extrusion Linear Lens

The most versatile modular product family especially designed for the application of office, warehouse, retail general lighting, shelf lighting and wall washing



Good covering effect

Customized length

Complete angle

High efficiency

OERSTED

OERSTED is a linear extrusion lenses family. The optics are made of diffused PMMA for high optical efficiency with good LED source hiding power. OERSTED can be customized for luminaires for different lengths

OERSTED-26


Width: 26mm, fit 24mm ZHAGA PCB, length customized, design for 3030 size LED package, compatible with 2835 size LED package.

Name	Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
OERSTED-26-45	26X1140	XX	45X90	91
OERSTED-26-60	26X1140	XX	60X90	90
OERSTED-26-70	26X1140	XX	70X90	92
OERSTED-26-90	26X1140	XX	90X90	88
OERSTED-26-110	26X1140	XX	110X90	88
OERSTED-26-140	26X1140	XX	140X90	84
OERSTED-26-165	26X1140	XX	165X130	90
OERSTED-26-DA25	26X1140	XX	Asymmetric	89
OERSTED-26-A15	26X1140	XX	Asymmetric	85

OERSTED-40

Width: 40mm, fit 24mm ZHAGA PCB, length customized, design for 3030 size LED package, compatible with 2835 size LED package.

Name		Dimensions	Led Qty	Typ.FWHM	Typ.Eff.
OERSTED-40-40	NEW	40X1140	XX	45X90	88
OERSTED-40-60	NEW	40X1140	XX	60X90	88
OERSTED-40-70	COMING	40X1140	XX	70X90	92
OERSTED-40-90	NEW	40X1140	XX	90X90	88
OERSTED-40-110	COMING	40X1140	XX	110X90	88
OERSTED-40-140	COMING	40X1140	XX	140X90	84
OERSTED-40-165	COMING	40X1140	XX	165X130	90
OERSTED-40-DA25	NEW	40X1140	XX	Asymmetric	88
OERSTED-40-A15	NEW	40X1140	XX	Asymmetric	88



Commercial Lighting

YOUYOU-G2

Optimizing the uniform light for multi-function down lighting.

YOUYOU-D28-G2

Ø28mm with holder, optimized for 4/6 mm LES size COB, with base

Name	D	H	Typ.FWHM	Typ.Eff.
YOUYOU-D28-12_G2	D28	16.1	12	80
YOUYOU-D28-24_G2	D28	16.1	24	80
YOUYOU-D28-36_G2	D28	16.1	36	80
YOUYOU-D28-50_G2	D28	16.1	50	80

YOUYOU-D35-G2

Ø35mm with holder, optimized for 4/6 mm LES size COB, with base

Name	D	H	Typ.FWHM	Typ.Eff.
YOUYOU-D35-15_G2	D35	19.7	15	90
YOUYOU-D35-24_G2	D35	19.7	24	90
YOUYOU-D35-36_G2	D35	19.7	36	90
YOUYOU-D35-50_G2	D35	19.7	50	90

YOUYOU-D45-G2

Ø45mm with holder, optimized for 6/9mm LES size COB, with base

Name	D	H	Typ.FWHM	Typ.Eff.
YOUYOU-D45-12_G2	D45	25.4	12	80
YOUYOU-D45-24_G2	D45	25.4	24	80
YOUYOU-D45-36_G2	D45	25.4	36	80
YOUYOU-D45-50_G2	D45	25.4	50	80

YOUYOU-D62-G2

Ø62mm with holder, optimized for 9/11mm LES size COB, with base

Name	D	H	Typ.FWHM	Typ.Eff.
YOUYOU-D62-12_G2	D62	30	12	80
YOUYOU-D62-24_G2	D62	30	24	90
YOUYOU-D62-36_G2	D62	30	36	90



YOUYOU-D28-G2



YOUYOU-D35-G2



YOUYOU-D45-G2



YOUYOU-D62-G2

DALTON

Deep concave surface structure to achieve the ultimate anti-glare effect, mainly optimized for high requirement of anti-glare scene of track lighting, ceiling lighting, spot lighting, outdoor flood lighting etc.

DALTON-D22

Ø22mm with holder, compatible for up to 6mm LES size COBs

Name	D	H	Typ.FWHM	Typ.Eff.
DALTON-D22-15	D22	15.1	15	76
DALTON-D22-24	D22	15.1	24	77
DALTON-D22-36	D22	15.1	36	78
DALTON-D22-50	D22	15.1	50	82

DALTON-D28

Ø28mm with holder, compatible for up to 6mm LES size COBs

Name	D	H	Typ.FWHM	Typ.Eff.
DALTON-D28-15	NEW D28	19.1	15	78
DALTON-D28-24	NEW D28	19.1	24	87
DALTON-D28-36	NEW D28	19.1	36	89
DALTON-D28-50	NEW D28	19.1	50	89



DALTON-D22



DALTON-D28

Commercial Lighting

DALTON-D35

Ø35mm with holder, optimized for 6mm LES size COB

Name	D	H	Typ.FWHM	Typ.Eff.
DALTON-D35-15	D35	23.6	15	90
DALTON-D35-24	D35	23.6	24	90
DALTON-D35-36	D35	23.6	36	90
DALTON-D35-50	D35	23.6	50	90



DALTON-D35

DALTON-D45

Ø45mm with holder, compatible for 9mm LES size COB

Name	D	H	Typ.FWHM	Typ.Eff.
DALTON-D45-15	D45	29.3	15	88
DALTON-D45-24	D45	29.3	24	92
DALTON-D45-36	D45	29.3	36	91
DALTON-D45-50	D45	29.3	50	90



DALTON-D45

DALTON-D55

Ø55mm with holder, compatible for 9mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
DALTON-D55-15	NEW	D55	35.6	15	89
DALTON-D55-24	NEW	D55	35.6	24	89
DALTON-D55-36	NEW	D55	35.6	36	89
DALTON-D55-50	NEW	D55	35.6	50	88



DALTON-D55

DALTON-D62

Ø62mm with holder, compatible for 12mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
DALTON-D62-15		D62	40	15	90
DALTON-D62-24		D62	40	24	90
DALTON-D62-36		D62	40	36	90
DALTON-D62-50		D62	40	50	90



DALTON-D62

DALTON-D75

Ø75mm with holder, optimized for 14.5mm LES size COBs

Name		D	H	Typ.FWHM	Typ.Eff.
DALTON-D75-15	NEW	D75	48.5	15	87
DALTON-D75-24	NEW	D75	48.5	24	90
DALTON-D75-36	NEW	D75	48.5	36	90
DALTON-D75-50	NEW	D75	48.5	50	89



DALTON-D75

Commercial Lighting

HUBBLE

Cutoff light COB Lens for track lighting.

HUBBLE-D43

Ø43mm with white base, optimized for 6/9 mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
HUBBLE-D43-12	NEW	D43	20.6	12	90
HUBBLE-D43-24	NEW	D43	20.6	24	90
HUBBLE-D43-36	NEW	D43	20.6	36	90
HUBBLE-D43-50	NEW	D43	20.6	50	90

HUBBLE-D69

Ø69mm with white base, optimized for 9/11 mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
HUBBLE-D68.9-12		D68.9	31.5	12	92
HUBBLE-D68.9-24		D68.9	31.5	24	92
HUBBLE-D68.9-36		D68.9	31.5	36	92
HUBBLE-D68.9-50		D68.9	31.5	50	92

HUBBLE-D75

Ø75mm with white base, optimized for 9/11 mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
HUBBLE-D75-10	NEW	D75	34.3	10	90
HUBBLE-D75-24	NEW	D75	35.4	24	90
HUBBLE-D75-36	NEW	D75	34.3	36	90

COMPTON

Ø50mm thinned COB lens, feature for convenient MR 16 size and ZHAGA light module, suitable for traditional MR16 luminaire update optics for down lights and compact tracklights, up to 21 mm LES size COBs

Name		D	H	Typ.FWHM	Typ.Eff.
COMPTON-20	COMING	D50	19.3	20	92
COMPTON-36	NEW	D50	19.3	36	88
COMPTON-50	COMING	D50	19.3	50	92
COMPTON-65	COMING	D50	19.3	65	92
COMPTON-60X20	COMING	D50	19.3	60X20	92

VOLTA

Economic solution Thinner COB lens, optimized for compact lighting(thinner track lighting & down lighting).

VOLTA-D70

Ø70mm, optimized for 14.5mm LES size COB

Name		D	H	Typ.FWHM	Typ.Eff.
VOLTA-D70-13	COMING	D70	11.8	13	90
VOLTA-D70-18	COMING	D70	12.8	18	90
VOLTA-D70-24	COMING	D70	12.8	24	90
VOLTA-D70-36	COMING	D70	12.8	36	90
VOLTA-D70-60	COMING	D70	12.8	60	90
VOLTA-D70-25X60	COMING	D70	12.8	25X60	90
VOLTA-D70-Asy	COMING	D70	11.8	Asymmetric	90



HUBBLE-D43



HUBBLE-D69



HUBBLE-D75



COMPTON



VOLTA

LED Backlight & TV Lens

KEPLER

Optimized for back light lens of panel lighting, ceiling lighting, advertising light box, made by PMMA.

Name		D	OD	LED spacing	Led	Typ.Eff.
KEPLER-D11.5	NEW	D11.5	20~30	Px80 , Py90	LUXEON 3030 SQUARE	90
KEPLER-D11.5		D11.5	20~30	Px80 , Py90	SAMSUNG 2835	93
KEPLER-D13.5	NEW	D13.5	20~30	Px80 , Py90	LUXEON 3030 SQUARE	90
KEPLER-D13.5		D13.5	20~30	Px80 , Py90	SAMSUNG 2835	93

KEPLER-T

TV Backlight (Refraction type)

Name		D	OD	LED spacing	Led	Typ.Eff.
KEPLER-T-D16	NEW	D15.8	35	Px105 , Py155	LUXEON 3030 SQUARE	90
KEPLER-T-D16	NEW	D16	35	Px94 , Py155	LUXEON 3030 SQUARE	90

KEPLER-F

TV Backlight (Reflection type)

Name		D	OD	LED spacing	Led	Typ.Eff.
KEPLER-F-D17	NEW	D17	18/22	Px145 , Py145	LUXEON 3030 SQUARE	90



KEPLER



KEPLER-T



KEPLER-F


Glass Light Lens

LIPPMANN

LIPPMANN-D78

Single glass lenses, Ø78 mm round lens optimized for 20mm LES size COB

Name		Dimensions	Height	Typ.FWHM	Led	Typ.Eff.
LIPPMANN-D78-36	NEW	D78	44.6	36	SAMSUNG LC080D	91
LIPPMANN-D78-45		D78	43.7	45	SAMSUNG LC080D	91
LIPPMANN-D78-60		D78	40	60	SAMSUNG LC080D	91
LIPPMANN-D78-90		D78	35	90	SAMSUNG LC080D	91
LIPPMANN-D78-100		D78	26.4	100	SAMSUNG LC080D	91
LIPPMANN-D78-120		D78	26.4	120	SAMSUNG LC080D	91




LIPPMANN-D78

LIPPMANN-D92

Single glass lenses, Ø92 mm round lens optimized for 20mm LES size COB

Name		Dimensions	Height	Typ.FWHM	Led	Typ.Eff.
LIPPMANN-D92-60	COMING	D92	312	60	SAMSUNG LC080D	91
LIPPMANN-D92-90	COMING	D92	312	90	SAMSUNG LC080D	91
LIPPMANN-D92-T1VS		D92	312	Asymmetric	SAMSUNG LC080D	91
LIPPMANN-D92-T1S		D92	312	Asymmetric	SAMSUNG LC080D	91
LIPPMANN-D92-T2VS		D92	34	Asymmetric	SAMSUNG LC080D	91
LIPPMANN-D92-T1M		D92	312	Asymmetric	SAMSUNG LC080D	91



LIPPMANN-D92


Glass Light Lens



ZEEMAN


ZEEMAN-10
143 x 82mm 10 arrays optimized for SMD 7070 size LED packages.

Name		Dimensions	Height	Typ.FWHM	Led	Typ.Eff.
ZEEMAN-10-60	COMING	143X82	10	60	SMD7070 SQUARE	95
ZEEMAN-10-90	COMING	143X82	10	90	SMD7070 SQUARE	95
ZEEMAN-10-T1S		143X82	10	Asymmetric	SMD7070 SQUARE	95
ZEEMAN-10-T2M		143X82	10	Asymmetric	SMD7070 SQUARE	95
ZEEMAN-10-T2VS		143X82	10	Asymmetric	SMD7070 SQUARE	95
ZEEMAN-10-T1VS		143X82	10	Asymmetric	SMD7070 SQUARE	95



ZEEMAN-12
143 x 82mm 12 arrays optimized for SMD7070 size LED packages

Name		Dimensions	Height	Typ.FWHM	Led	Typ.Eff.
ZEEMAN-12-60		143X82	12	60	SMD7070 SQUARE	95
ZEEMAN-12-90		143X82	12	90	SMD7070 SQUARE	95



Why Sunlumin

Pre-sale Technical Support & After-sales Service



On field technical support




24 hours technical and after-sales service assistance from China HQ customer service department


R&D ability

- 1 Rich experience in optical design of street lights for Brazil(INMETRO), India (NHAI), Russia , Australia , Europe ,Turkey
- 2 RGBW ultra-uniform combining optical design
- 3 Expertise in professional sport light projects
- 4 Ultra-small angle optical design high accuracy
- 5 Base on housing or heat sink, we can provide lens mechanical design and offer lens 3D files
- 6 We offer service for verifying lighting solutions particular to DIALUX / AGI32

Road light distribution simulation



Light distribution curve



Quality Assurance

- 1 Lens protection grade test
- 2 Accuracy photoelectric parameters test
- 3 Lens reliability testing
- 4 SGS ISO9001:2008; Quality assurance service up to 5-10 years

Delivery Assurance

- 1 Available local production in main market
- 2 Swift and precise delivery control
- 3 Accessible local stock in main market

- ◆ Optic Design
- ◆ Lighting Simulation
- ◆ Mechanical Design



www.sunlumin-optics.com
info@sunlumin-optics.com



www.sunlumin-optics.com