

# DATASHEET

S01.01.02.417\_SNELL-15\_5050

## Architecture Lighting:

~15° extra narrow beam with holder.


### 1.General Information

Lens Material	: PMMA
Holder Material	: PC
Size	: Ø 16MM
typ.FWHM	: 15°
Design LED	: CREE XPG3
Compatibility	: 5050/3535/3030/2835
typ.Efficiency	: 80%
Fasten	: Tape
IP class	: N/A
Zhaga	: N/A
RoHS	: YES
Color	: Clear



### 2.MECHANICAL SPECIFICATION

UNIT:mm



Dimensions with unmarked tolerances refer to GBT14486 tolerance table.

### 3. OPTICAL RESULTS


#### 1) PHOTOMETRIC DATA(MEASURED):



LED model	CREE XPG3
Light colour	White
LEDs/each optic	1
FWHM	H17.6°,V17.5°
FWTM	H35.3°,V35.4°

Required components:

N/A




#### 2) PHOTOMETRIC DATA(MEASURED):



LED model	Luxeon 5050 HE
Light colour	White
LEDs/each optic	1
FWHM	H24.3°,V25.2°
FWTM	H56.5°,V54.9°

Required components:

N/A



### 4.Usage and Maintenance

- 1) If necessary, clean lenses with mild soap, water and soft cloth.
- 2) Never use any commercial cleaning solvents on lenses, like alcohol.
- 3) Please handle lens with wearing gloves, skin oils may damage lens or its optical characteristic.

### 5.Note

Please test the data again before using. The chart data is for reference only.

The appearance and specifications of the product can be changed to improve the quality and/or performance without notice.

Last update: 2025-2-24